

SEDIMENT CARTRIDGES



SYSTEM - GUARD™ DEPTH FILTER CARTRIDGES

SWT's System-Guard™ Filter Cartridges have 65% more dirt-holding capacity than standard spun polypropylene cartridges. New microfiber technology provides a tightly controlled graduated microporous structure for greater filtration efficiency¹ with less pressure drop² than any other spun polypropylene cartridge.

This is the best performing sediment depth cartridge SWT has ever offered and is FDA compliant. It is specifically designed as a reverse osmosis prefilter, but can be used in all water treatment applications.

1. 90% @ cartridge's micron rating.
2. 5 micron Cartridges: Less than 0.6 psid @ 5 gpm per 10 inch length in clear water
1 micron Cartridges: Less than 0.9 psid @ 5 gpm per 10 inch length in clear water



Part Number	Description	Micron (Nominal)	Case Qty	Weight Lbs.
-------------	-------------	------------------	----------	-------------

System-Guard™ Sediment Cartridges, 2.5 x 9.875 inch, to fit most standard 10 inch housings

SO62001	Thermally-Welded Blown Polypropylene Microfibers	1	40	10
SO62005	Thermally-Welded Blown Polypropylene Microfibers	5	40	10

System-Guard™ Sediment Cartridges, 2.5 x 20 inch, to fit most standard 20 inch housings

SO72001	Thermally-Welded Blown Polypropylene Microfibers	1	20	19
SO72005	Thermally-Welded Blown Polypropylene Microfibers	5	20	19

System-Guard™ Sediment Cartridges, 2.5 x 30 inch, to fit most standard 30 inch housings

SO82001	Thermally-Welded Blown Polypropylene Microfibers	1	20	28
SO82005	Thermally-Welded Blown Polypropylene Microfibers	5	20	28

System-Guard™ Sediment Cartridges, 2.5 x 40 inch, to fit most standard 40 inch housings

SO92001	Thermally-Welded Blown Polypropylene Microfibers	1	20	37
SO92005	Thermally-Welded Blown Polypropylene Microfibers	5	20	37

Cartridge lengths of 9.75, 10, 19.5, and 29.25 inch are also available. Contact SWT for pricing.