

INDUSTRIAL VALVE CONTROLS



FILTER & SOFTENER CONTROLLERS & STAGERS

Filters — Time Initiated Controller with Stager

Part Number	Description
A148-01	Filter, 3 Cycle, Single Tank
A151-10	Filter, 3 Cycle, Two Tank Parallel with Sequential Backwash
A158-03	Filter, 3 Cycle, Three Tank Parallel with Sequential Backwash
A158-04	Filter, 3 Cycle, Four Tank Parallel with Sequential Backwash

Please specify voltage requirement: 115VAC/60Hz standard; 220VAC/50Hz or 220VAC/60Hz available at additional cost.
Please specify if a 6-day or 7-day clock timer is required. If not specified, a 6-day timer is supplied.

Filters — Demand/Metered Initiated 962 Controller with Stager (Flow Meter Not Included — See Back)

Part Number	Description
E948-01	Filter, 3 Cycle, Single Tank
E951-10	Filter, 3 Cycle, Two Tank Parallel with Sequential Backwash
E958-03	Filter, 3 Cycle, Three Tank Parallel with Sequential Backwash
E958-04	Filter, 3 Cycle, Four Tank Parallel with Sequential Backwash

Optional Relay Output available (on single units only).
PWA Circuit Board and Key Pad Assembly available (P/N: QA-1078458).
Battery back-up capable: 9-volt rechargeable battery sold separately (P/N: UA-1075768).
Please specify voltage requirement: 120VAC/50-60Hz standard; 220VAC/50-60Hz available at no extra charge.

Softeners — Time Initiated Controller with Stager

Part Number	Description
A148-00	Softener, 4 Cycle, Single Tank
A158-TA	Softener, Twin Alternating

Please specify voltage requirement: 115VAC/60Hz standard; 220VAC/50Hz or 220VAC/60Hz available at additional cost.
Please specify if a 6-day or 7-day clock timer is required. If not specified, a 6-day timer is supplied.

Softeners — Demand/Metered Initiated 962 Controller with Stager (Flow Meter Not Included — See Back)

Model Number	Description
E948-00	Softener, 4 Cycle, Single Tank
E951-07	Softener, 5 Cycle, Single Tank with Timed Brine
E951-09	Softener, 5 Cycle, Single Tank with Timed Refill
E951-06	Softener, 6 Cycle, Single Tank with Timed Brine and Refill
E958-TA	Softener, Twin Alternating with 2 Status Lights
E958-TB	Softener, Twin Alternating with Timed Brine, No Status Lights
E958-SS	Softener, Twin Alternating with Rinse Down Feature and 2 Status Lights

Optional Relay Output available (on single units only).
PWA Circuit Board and Key Pad Assembly available (P/N: QA-1078458).
Battery back-up capable: 9-volt rechargeable battery sold separately (P/N: UA-1075768).
Please specify voltage requirement: 120VAC/50-60Hz standard; 220VAC/50-60Hz available at no extra charge.

INDUSTRIAL VALVE CONTROLS



FILTER & SOFTENER FLOW METERS

GE Osmonics Flow Meters

Part Number	Description	Flow Rate (Min / Max / Peak)
UA-3023532	1 inch Flow Meter with Stainless Steel NPT Adapters	0.25 / 35 / 40
UA-3023536	2 inch Flow Meter with Stainless Steel NPT Adapters	2 / 170 / 250

Flow Cell Flow Meters

(X = Available)

Pipe Size Inches (mm)	Female Threaded (NPT or BSP)		Flange Mounting (Gaskets Included, Flanges Sold Separately)		
	Cast Iron	316 S.S.	Cast Iron	316 S.S.	PVC
0.375 (10)	X	X			X
0.5 (15)	X	X			X
0.75 (20)	X	X			X
1 (25)	X	X			X
1.25 (32)	X	X			X
1.5 (40)	X	X	X	X	X
2 (50)	X	X	X	X	X
2.5 (65)	X	X	X	X	X
3 (80)	X	X	X	X	X
4 (100)	X	X	X	X	X
5 (125)	X	X	X	X	X
6 (150)	X	X	X	X	X
8 (200)			X	X	X
10 (250)			X	X	X
12 (300)			X	X	X

14 thru 24 inch (350 thru 600 mm) pipe size available, call for details.