

AIR INJECTORS



AIR INJECTORS WITH BYPASS LOOP



HORIZONTAL INSTALLATION



V
E
R
T
I
C
A
L

I
N
S
T
A
L
L
A
T
I
O
N

SWT Air Injectors are preassembled to save you time and energy in the field. Air injection is the chemical free way to oxidize dissolved iron and sulfide in the water. These air injectors can be used in combination with FiltrEase™, Carbon, and Metalease™ Filter Systems to greatly enhance their performance as well.

These air injectors are normally installed in-line between the pump and the well tank, and draw air into the system as the pump cycles. The venturi features easy disassembly using true union connectors for scheduled cleaning.

- Designed for most residential well applications
- 3/4 inch or 1 inch connections
- Great companion piece for SWT MetalEase™ Filters or Magnum Accelerators™
- Easy to clean venturi
- Easy installation
- Fully adjustable setting for all residential well applications

Air Injector with Bypass Loop

Part Number	Description	Operating Pressure	Flow Range	Connection
MICRO-3/4	Air Injector Assembly PVC	10 to 60 PSI	5 to 15 GPM	3/4 inch
MICRO-1	Air Injector Assembly PVC	10 to 60 PSI	5 to 15 GPM	1 inch
IM-SSF1	Air Injector Only (no assembly)	10 to 60 PSI	5 to 15 GPM	1 inch NPT
SE-ZEA122A116	Honeywell Air Vent (optional)	—	—	1/8 inch