


# PRESSURE VESSEL FITTINGS




## FLANGES & ADAPTERS

### Threaded Adapters (2.5"-8 NPSM)




Part No.	Reduced To . . .	Material	Max. Temperature	Max. Pressure
TS-2751-3	0.75" NPT	PVC	120°F	150 PSI
TS-2751-5	1" NPT	PVC	120°F	150 PSI
TS-2751-8	1.25" NPT	PVC	120°F	150 PSI
TS-2751-4	1.5" NPT	PVC	120°F	150 PSI
TS-2751-6	2.25"-16 NPSM	PVC	120°F	150 PSI

### Threaded Adapters (4"-8 UN)



Part No.	Reduced To . . .	Material	Max. Temperature	Max. Pressure
TS-4821-6	1" NPT	CPVC	150°F	150 PSI
TS-4821-12	1.25" NPT	CPVC	150°F	150 PSI
TS-4821-7	1.5" NPT	CPVC	150°F	150 PSI
TS-4821-8	2" NPT	CPVC	150°F	150 PSI
TS-4821-17	2"-11.5 NPSM	CPVC	150°F	150 PSI
TS-4821-2	2.5"-8 NPSM	CPVC	150°F	150 PSI
TS-4821-4	3"-8 UN	CPVC	150°F	150 PSI

### Threaded Adapters (6"-8 UN)



Part No.	Reduced To . . .	Material	Max. Temperature	Max. Pressure
TS-4125-003	3" FPT	NORYL	150°F	150 PSI
SM-TR468	4"-8 UN	PVC	120°F	150 PSI

### SNA Flanged Adapters (6" SNA)



Part No.	Adapt To . . .	Material	Max. Temperature	Max. Pressure
TS-5292	3" NPT to 3" NPT	NORYL	150°F	150 PSI
TS-5267	3" NPT to 3" NPT	NORYL	150°F	150 PSI
TS-5295	3" NPT to 4"-8 UN	NORYL	150°F	150 PSI
TS-10566	4"-8 UN	NORYL	150°F	150 PSI
TS-10659	1" NPT	CPVC	150°F	150 PSI
TS-10660	1.5" NPT	CPVC	150°F	150 PSI
TS-10661	2" NPT	CPVC	150°F	150 PSI
TS-10662	3" NPT	CPVC	150°F	150 PSI
TS-10663	4" NPT	CPVC	150°F	150 PSI
SM-FLGRD64	4"-8 UN	PVC	120°F	150 PSI

### ANSI Flanged Adapters (4" ANSI)



Part No.	Adapt To . . .	Material	Max. Temperature	Max. Pressure
TS-5276	3" NPSM	CPVC	150°F	150 PSI
TS-10673	2" NPT	CPVC	150°F	150 PSI
TS-10674	3" NPT	CPVC	150°F	150 PSI

# PRESSURE VESSEL FITTINGS



## CLOSURES & ADAPTERS

### Threaded Closures



Part Number	Opening	Material	Max. Temp.	Max. Pressure
LC-Q7006	1.25" NPSM	Polyglass	120°F	150 PSI
TS-2751-1	2.5"-8 NPSM	PVC	120°F	150 PSI
SM-CL258	2.5"-8 NPSM	PVC	120°F	150 PSI
LC-Q7004	2.5"-8 NPSM	ABS	120°F	120 PSI
TS-4821-1	4"-8 UN	CPVC	150°F	150 PSI
SM-CL48	4"-8 UN	PVC	120°F	150 PSI
TS-2695-1	6"-8 UN	CPVC	150°F	150 PSI
SM-CL6	6"-8 UN	PVC	120°F	150 PSI

### Flanged Closures



Part Number	Flange Size	Material
TS-5259	4" ANSI	CPVC
TS-10472	4" ANSI	ACRYLIC
TS-5296	6" SNA	NORYL
TS-10658	6" SNA	CPVC

### Manway Closures/Adapters




Part Number	Opening	Reduced To ...	Material	Max. Temperature	Max. Pressure
TS-10108	16" Manway	2" NPT	Vinylester	150°F	150 PSI
TS-10582	16" Manway	2" NPT	CPVC	150°F	100 PSI
TS-10584	16" Manway	4" NPT	CPVC	150°F	100 PSI
TS-11294	16" Manway	3" NPT to 3" NPT	CPVC	150°F	100 PSI

# PRESSURE VESSEL FITTINGS




## FLEX CONNECTORS, VACUUM BREAKERS, AND SIDE ADAPTERS

### Flex Connector Assembly (NPT x NPT)



Part Number	Description	Max. Temperature	Max. Pressure
NI-5285	2" MNPT x 2" MNPT, 14" Overall Length	150°F	150 PSI
NI-5286	3" MNPT x 3" MNPT, 14" Overall Length	150°F	150 PSI
TS-5285	2" MNPT x 2" MNPT, 12" Overall Length	150°F	150 PSI
TS-5286	3" MNPT x 3" MNPT, 12" Overall Length	150°F	150 PSI

### Flex Connector Assembly (Flanged)



Part Number	Description	Max. Temperature	Max. Pressure
TS-5239	4" Flange to 3" MNPT	150°F	150 PSI

### Connector



Part No.	Description
TS-5045	3" NPSM x 3" NPT (CPVC) 150 PSI / 150°F



### Elbow

Part No.	Description
TS-5201	2" NPSM to 2" Slip (CPVC) 150 PSI / 150°F


### Vacuum Breakers



Part Number	Connection	Max. Temperature	Max. Pressure
TS-10724	1.5" FNPT	120°F	125 PSI
SM-VB4P	1.5" FNPT	140°F	125 PSI
TS-10725	1" FNPT	150°F	150 PSI

### Wrenches

Part No.	Connection
TS-6568-2	4" Closure (4825-1)
TS-7729	6" Closure (2695-1)



### Brass Side Adapters



Part Number	Description	Max. Temperature	Max. Pressure
TS-1661	0.75" NPT to 0.75" FNPT	150°F	150 PSI
TS-2829	1.5" NPT to 1.5" FNPT	150°F	150 PSI