

# FILTER HOUSINGS



## STAINLESS STEEL FILTER HOUSINGS



### Stainless Steel Filter Housing for High Temperatures

Part Number*	Number of 10 inch Cartridges	Standard Connect Size	Drain Size	Maximum Flow Rate GPM (LPM)	Housing Dimensions Inches	Shipping Weight Lbs.
YH22401	1	3/4" FPT	1/8" NPT	8 (30)	3.5 x 14	6
YH22501	1	1" FPT	1/8" NPT	8 (30)	3.5 x 14	6
YH22402	2	3/4" FPT	1/8" NPT	16 (60)	3.5 x 24	8
YH22502	2	1" FPT	1/8" NPT	16 (60)	3.5 x 24	8
YH22403	3	3/4" FPT	1/8" NPT	24 (90)	3.5 x 33	11
YH22503	3	1" FPT	1/8" NPT	24 (90)	3.5 x 33	11

\* Add a "-S" after the part number for 316L stainless steel models.  
All models include mounting bracket and screws.  
3/8 and 1/2 inch connections available for 1- and 2-cartridge models.



### Stainless Steel Filter Housing for High Flow Rate and High Temperatures

Part Number*	Number of 10 inch Cartridges	Standard Connect Size	Drain Size	Maximum Flow Rate GPM (LPM)	Housing Dimensions Inches	Shipping Weight Lbs.
YH22704	4	2" MPT	1/2" NPT	32 (121)	10.5 x 20	25
YH22705	5	2" MPT	1/2" NPT	40 (151)	10.5 x 20	27
YH22708	8	2" MPT	1/2" NPT	64 (242)	10.5 x 30	31
YH22710	10	2" MPT	1/2" NPT	80 (303)	10.5 x 30	33
YH22712	12	2" MPT	1/2" NPT	96 (363)	10.5 x 40	38
YH22715	15	2" MPT	1/2" NPT	120 (454)	10.5 x 40	38
YH22716	16	2" MPT	1/2" NPT	128 (485)	10.5 x 50	45
YH22720	20	2" MPT	1/2" NPT	160 (606)	10.5 x 50	45
YH22724	24	3" Flange	1/2" NPT	192 (727)	16.5 x 40	56
YH22728	28	2" MPT	3/4" NPT	224 (848)	12.5 x 50	66
YH22736	36	3" Flange	3/4" NPT	288 (1,090)	16.5 x 50	92
YH22748	48	4" Flange	3/4" NPT	384 (1,454)	16.5 x 60	100
YH22766	66	4" Flange	3/4" NPT	528 (1,999)	20.5 x 39	140
YH22788	88	4" Flange	3/4" NPT	704 (2,665)	20.5 x 59	165

\* Add a "-S" after the part number for 316L stainless steel models.  
222/Fin and 226/Fin cartridge connections are available.

### High Flow Housing Options

Part Number*	Description
YH-LEGS-2IN	Support Legs — 2.5 inch, Welded, Sheet Metal Legs
YH-LEGS-6IN-HD	Support Legs — 6 inch, Heavy Duty, Angle Legs
YH-LEGS-MNT	Mounting Tabs — 1.125 inch, Bolted-on, Housing Tabs

\* Add a "-S" after the part number for 316L stainless steel models.

**Operating Temperature Range:** 40 to 300°F (4 to 149°C)  
**Maximum Operating Pressure:** 300 psi (20.7 bar) for 1- and 2-cartridge models  
150 psi (10 bar) for 3- or more cartridge models