

COMPOSITE PRESSURE TANKS



FIBERGLASS WRAPPED WITH ABS LINERS



Features

- Inner shell is blow molded from engineering grade plastic (ABS)
- Wound with continuous fiberglass to provide superior strength under pressure
- Corrosion free
- 150 psi maximum operating pressure
- 120°F maximum operating temperature
- ANSI/NSF certified to Standard 44
- Available in natural, almond, blue, black, or gray
- Made in Mexico (F.O.B. Chardon, OH)
- 10 year warranty for tanks up to 13 inch in diameter
- 5 year warranty for tanks over 13 inch in diameter

Warranty

Park pressure vessels are warranted to be free of manufacturing and material defects for a period of 10 years if operated within specifications in residential (up to 13 inch diameter) water treatment applications. Commercial and industrial sizes (above 13 inch diameters) are warranted for a period of 5 years. Warranty coverage excludes freezing, vacuum, corrosive materials exposure.

Part Number	Tank Size Inches	Top Opening Inches	Base Style	Volume Cu. Ft.	Carton Qty.	Carton Weight Lbs.
IP0618C20*	6 x 18	2.5	Standard	0.27	10	47.6
IP0818C20*	8 x 18	2.5	Standard	0.47	8	48.0
IP0830C20*	8 x 30	2.5	Standard	0.81	4	34.8
IP0844C20*	8 x 44	2.5	Standard	1.25	18	214.2
IP0942C20*	9 x 42	2.5	Standard	1.41	4	51.0
IP1040C20*	10 x 40	2.5	Standard	1.60	12	162.0
IP1054C20*	10 x 54	2.5	Standard	2.20	16	278.0
IP1236C20*	12 x 36	2.5	Standard	2.19	1	20.6
IP1236C50*	12 x 36	4.5	Standard	2.19	1	20.6
IP1242C20*	12 x 42	2.5	Standard	2.61	1	21.8
IP1242C40*	12 x 42	4.0	Standard	2.61	1	21.8
IP1242C50*	12 x 42	4.5	Standard	2.61	1	21.8
IP1252C20*	12 x 52	2.5	Standard	3.32	9	234.0
IP1252C40*	12 x 52	4.0	Standard	3.32	9	234.0
IP1252C50*	12 x 52	4.5	Standard	3.32	9	234.0
IP1447C20*	14 x 47	2.5	Standard	3.60	1	31.8
IP1447C40*	14 x 47	4.0	Standard	3.60	1	31.8
IP1447C50*	14 x 47	4.5	Standard	3.60	1	31.8

* Specify color: 'A'=Almond; 'B'=Blue; 'G'=Gray; 'K'=Black; 'N'=Natural. If not specified, SWT will supply Black or Natural. Call for availability of dome holes, side holes, bottom holes, and other options.