

# RESIDENTIAL FILTEREASE-HD™ FILTERS



## SWT POINT-OF-ENTRY SEDIMENT FILTERS



Safe Water Technologies' Residential Sediment Filters are built utilizing SWT's FilterEase-HD™ filter media. These filters are designed to remove ferric iron, silt, and turbidity, and are preferred when higher backwash rates (if available) are desired for cleaning iron and silt from the filter bed. Sediment filtration as low as 10 to 20 micron is common. Plus, these systems feature SWT's Cyclonic Distributor System™ to provide full bed contact, less channeling, and superior backwashing (see reverse side).

- **Better filtration** than sand — Nominal **20 micron** (or better) filtration
- **50% less water for backwashing** than sand filters
- **Fully programmable, energy efficient controller** uses less than \$5.00 of electricity per year
- **100% corrosion-free** system
- Choice of **piston driven (Tech Series)** or **cam driven (Logix Series)** valves

Part Number	Tank Size Inches	Service Flow Rate*		Backwash 40% Exp. @ 60°F GPM (LPM)	Standard Connection Size
		Standard GPM (LPM)	Peak GPM (LPM)		

### Tech Series Automatic Backwashing FilterEase-HD™ Filters

FHA075C	8 x 44	3-6 (11-23)	6 (23)	5.0 (18.9)	1 inch Brass Sweat
FHA100C	9 x 48	4-7 (15-26)	8 (30)	7.0 (26.5)	1 inch Brass Sweat
FHA150C	10 x 54	4-9 (15-34)	12 (45)	8.0 (30.3)	1 inch Brass Sweat
FHA200C	12 x 52	5-10 (19-38)	15 (57)	12.0 (45.4)	1 inch Brass Sweat
FHA250C	13 x 54	6-12 (23-45)	18 (68)	15.0 (56.8)	1 inch Brass Sweat
FHA300C	13 x 65	6-12 (23-45)	18 (68)	15.0 (56.8)	1 inch Brass Sweat
FHA350C	14 x 65	7-14 (26-53)	21 (80)	15.0 (56.8)	1 inch Brass Sweat

### Logix Series Automatic Backwashing FilterEase-HD™ Filters

FHA075L	8 x 44	3-6 (11-23)	6 (23)	5.0 (18.9)	1 inch Copper Tube
FHA100L	9 x 48	4-7 (15-26)	8 (30)	7.0 (26.5)	1 inch Copper Tube
FHA150L	10 x 54	4-9 (15-34)	12 (45)	8.0 (30.3)	1 inch Copper Tube
FHA200L	12 x 52	5-10 (19-38)	15 (57)	12.0 (45.4)	1 inch Copper Tube
FHA250L	13 x 54	6-12 (23-45)	18 (68)	15.0 (56.8)	1 inch Copper Tube
FHA300L	13 x 65	6-12 (23-45)	18 (68)	15.0 (56.8)	1 inch Copper Tube
FHA350L	14 x 65	7-14 (26-53)	21 (80)	15.0 (56.8)	1 inch Copper Tube

\* For superior filtration, reduce flow rates by 1/3 of the standard flow rate specification.

Tank jackets available, see reverse side.

International voltages available at additional cost.

All systems have other piping connections available. See the Control Valve Price Lists for more details.

**Operating Pressure:** 20 to 125 psi (1.4 to 8.6 bar)

**Operating Temperature:** 36 to 120°F (2 to 48.9°C)

All pressure vessels are wound fiberglass composite tanks with copolymer polypropylene liner and are NSF® listed.

**Duplex systems available, call for details.**

10 year warranty on tank, 5 year warranty on valve.

# RESIDENTIAL FILTEREASE-HD™ FILTERS



## SWT POINT-OF-ENTRY SEDIMENT FILTERS

### OPTIONAL CHROME TANK JACKET



No unsightly exposed tank neck

Durable textured black cover

Made of high-impact polystyrene for exceptional strength and durability

Fully insulated to add protection to the tank and eliminate condensation

Attractive high gloss chrome finish

Light weight and easy to install

Resists UV degradation

### Options

Part Number	Description
RG-TJ0844EC	Chrome Tank Jacket, 8 x 44 inch
RG-TJ0948EC	Chrome Tank Jacket, 9 x 48 inch
RG-TJ1054EC	Chrome Tank Jacket, 10 x 54 inch
RG-TJ1252EC	Chrome Tank Jacket, 12 x 52 inch
By Request	Substitute 0.75 Copper Fittings
By Request	Substitute 0.75 or 1 inch PVC Socket Fittings
By Request	Substitute 0.75 or 1 inch PVC NPT Fittings
By Request	Substitute 0.75 or 1 inch Brass NPT Fittings



### SWT Treatment Systems Now Include **CYCLONIC DISTRIBUTOR SYSTEM™**

- Up to 30% less backwash flow rate is required...conserving water for the customer.
- Distributor plate is designed for more than 6,500 lbs load capacity.
- Reduces system pressure loss while increasing flow and efficiency through the bed.
- Available for 7, 8, 9, 10, 12, 13, 14, and 16 inch systems.

SWT's Cyclonic Distributor System™ (CDS) is a built-in bottom plate distributor which offers significant advantages over standard distribution systems — from the elimination of gravel underbedding (reducing overall cost and shipping weight) to the permanent attachment of the riser tube and distributor plate (eliminating re-bedding when servicing the valve).

This environmentally friendly design offers the most efficient service and backwashing characteristics available — reducing the amount of water to drain in backwash, while increasing the overall filtration capacity of a system.