

CONTROL VALVES



TECH-EE SERIES CONTROL VALVES COMMERCIAL / INDUSTRIAL APPLICATIONS WITH 2 INCH INTERNAL PORTING



OPTIONAL 2 INCH METER

- Service flow rate 115 gpm, backwash flow rate 80 gpm
- Epoxy coated lead-free brass valve body
- Economical stainless steel optional meter assembly
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate, and total volume used (totalizer)
- Four methods to initiate regeneration: meter immediate, meter delayed, time clock delayed, or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability, and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow or upflow brining, slow rinse, second backwash, fast rinse, refill, and downflow service
- Coin cell lithium battery backup with an eight hour carry over
- Level VI 15-volt output DC power supply provides safe and easy installation
- Post treated water regenerant refill
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drives
- Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine, and chloramines
- Certified to NSF/ANSI 61 and 372

CONTROL VALVES



TECH-EE SERIES CONTROL VALVES COMMERCIAL / INDUSTRIAL APPLICATIONS WITH 2 INCH INTERNAL PORTING

SPECIFICATIONS

Inlet/Outlet	2 inch FNPT
Cycles	Up to 6
Valve Material	Lead-free brass
Regeneration	Downflow

FLOW RATES

Service @15 psi drop (includes meter)	115 gpm
Backwash @ 25 psi drop	80 gpm
Cv Service	29.7
Cv Backwash	16.0

OPERATING PRESSURES

Minimum/Maximum	20 to 125 psi
-----------------	---------------

OPERATING TEMPERATURES

Minimum/Maximum	40 to 110° F
-----------------	--------------

METER

Accuracy	± 5%
Flow Rate Range	1.5 to 150 gpm
Gallon Range	20 to 1,500,000 gallons
Totalizer	1 to 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot	1.90 inch OD (1-1/2 inch NPS)
Drain Line ¹	1-1/2 inch FNPT
Brine Line Adapters Included	1 inch MNPT elbow, 3/4 x 1 inch solvent weld elbow, 1/2 inch OD poly tube compression
Mounting Base	4"-8 UN
Height from Top of Tank	8-1/2 inch
Shipping Weight with Meter	29 lb

ELECTRICAL SPECIFICATIONS (Power Supply)

	USA	International
Supply Voltage	100 VAC to 120 VAC	200 VAC to 240 VAC
Supply Frequency	50/60 Hz	50/60 Hz
Output Voltage	15 VDC	15 VDC
Output Current	500 mA	500 mA

TANK APPLICATIONS

Water Softener	12 to 48 inch diameter
Water Filter ²	12 to 30 inch diameter

CYCLES OF OPERATION

Cycle	Softener	Filter
1. Backwash 1st (upflow)	1 to 95 minutes	1 to 95 minutes
2. Regenerate Draw/Slow Rinse (downflow)	1 to 180 minutes	
3. Backwash 2nd (upflow)	1 to 95 minutes	
4. Fast Rinse (downflow)	1 to 95 minutes	1 to 95 minutes
5. Regenerant Refill (in service with treated water)	0.1 to 99.0 or off	
6. Service (downflow)		

OPTIONS

2 inch Stainless Steel Meter Assembly, Backwash Filter, Weather Cover

1. Drain line adapters are not included.

2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area.