

FILTRATION MEDIA



IRON REMOVAL COMPARISON CHART

Iron Removal Comparison Chart							
Media Name	Fe ⁺²	Fe ⁺³	Fe ₂ O ₃	Organic Iron	Ferrous Capacity mg/cu.ft.	pH Range	Active Manganese
MetalEase-AS™	Yes	Yes	Yes	Bulk	≥ 312,000	5 to 9	≥ 90%
MetalEase™	Yes	Yes	Yes	Bulk	[1]	5 to 9	≥ 74%
ProSoft™ Premium or ProSoft™ Gold [2]	Yes [3]	No	Slight	No	[3]	1 to 12	N/A
ProSelect™ Tannin-HP	N/A	N/A	Slight	Yes [4]	N/A	1 to 14	N/A
Greensand	Yes	Yes	Yes	Slight	≥ 16,000	6.6 to 8.0	0.5 to 1.0%
GreensandPlus™	Yes	Yes	Yes	Slight	≥ 16,000	6.2 to 8.5	3.2 to 4.8%
Filter-Ox™	Yes	Yes	Yes	Slight	N/A	6.2 to 8.5	12.5%
Birm®	Yes	Yes	Yes	No	≥ 566	6.6 to 8.0 [5]	2.3%
Zeolite-61	N/A	Yes	Yes	No	N/A	[6]	N/A
FilterEase™ or FilterEase-HD™	N/A	Yes	Yes	No	N/A	[6]	N/A

[1] Application dependent.

[2] Sodium form.

[3] 5 ppm maximum total iron level typical.

[4] Compatible for adding to softener bed.

[5] Requires dissolved oxygen to be 15 percent of the iron level.

[6] Wide range.