

SEDIMENT CARTRIDGES



SPUN POLYPROPYLENE SEDIMENT CARTRIDGES

These 100% polypropylene cartridges are SWT's lowest priced sediment cartridges. They are free of antistatic agents and binders eliminating the need for pre-rinsing. They are thermally-bonded to keep particles trapped in the filter, even under pressure, for consistent quality over its entire lifetime.

Max. Operating Temperature (water): 160°F (71°C) @ 15 psid (1.03 bar)

Max. Operating Differential Pressure (water): 35 psid (2.41 bar) @ 100°F (38°C)



Part Number	Description	Micron (Nominal)	Case Qty	Weight Lbs.	Cubic Feet
-------------	-------------	------------------	----------	-------------	------------

Spun Sediment Cartridges, 2.5 x 9.875 inch, to fit most standard 10 inch housings

SO60001	Spun Polypropylene Sediment Cartridge	1	40	21	1.7
SO60003	Spun Polypropylene Sediment Cartridge	3	40	20	1.7
SO60005	Spun Polypropylene Sediment Cartridge	5	40	19	1.7
SO60010	Spun Polypropylene Sediment Cartridge	10	40	18	1.7
SO60020	Spun Polypropylene Sediment Cartridge	20	40	17	1.7
SO60030	Spun Polypropylene Sediment Cartridge	30	40	16	1.7
SO60050	Spun Polypropylene Sediment Cartridge	50	40	15	1.7
SO60075	Spun Polypropylene Sediment Cartridge	75	40	14	1.7

Spun Sediment Cartridges, 2.5 x 20 inch, to fit most standard 20 inch housings

SO70001	Spun Polypropylene Sediment Cartridge	1	20	21	1.7
SO70003	Spun Polypropylene Sediment Cartridge	3	20	20	1.7
SO70005	Spun Polypropylene Sediment Cartridge	5	20	19	1.7
SO70010	Spun Polypropylene Sediment Cartridge	10	20	18	1.7
SO70020	Spun Polypropylene Sediment Cartridge	20	20	17	1.7
SO70030	Spun Polypropylene Sediment Cartridge	30	20	16	1.7
SO70050	Spun Polypropylene Sediment Cartridge	50	20	15	1.7
SO70075	Spun Polypropylene Sediment Cartridge	75	20	14	1.7

Above cartridges are also available in other materials with a variety of core materials. Contact your SWT representative for details.