

ABSOLUTE CARTRIDGES



SPECIFICATIONS

Diameter

Outside: 2.75 inch (70 mm)
Inside: 1.25 inch (31 mm)

Effective Filtration Area

8.1 sq.ft. (0.75 sq.m)

Materials of Construction

Filter Media: Hydrophilic
polyethersulfone membrane
Media Support: Polypropylene
microfiber
Components: Polypropylene

Max Operating Temperature (water)

180°F (82°C) @ 10 psid (0.7 bar)

Maximum Differential Pressure

Forward: 60 psi (4.1 bar) @ 70°F (21°C)
Reverse: 30 psi (2.1 bar) @ 70°F (21°C)

Integrity Testing

0.03 µm: ≤ 45 cc/min @ 50 psig (3.4 bar)
0.1 µm: ≤ 45 cc/min @ 50 psig (3.4 bar)
0.2 µm: ≤ 19 cc/min @ 30 psig (2.1 bar)

APPLICATIONS

- Ultrapure semiconductor water
- UPDI water pad
- High purity chemicals
- Point of use applications


ADVANTAGES

- Pre-rinsed cartridge
- Sterilizable by steam or autoclave
- All materials meet FDA requirements for food contact (21CFR)
- Aqueous extracts contain less than 0.25 EU/ml
- Broad chemical compatibility
- Meets USP24 Class VI-121°C criteria
- Passes MEM Elution Cytotoxicity Test
- The filters rinse to less than 5 ppb TOC and less than 5 ppb trace metals in 25 min at 2.5 gpm per 10 inch module in UPDI water.
- 100% Integrity tested

MPE SERIES PES MEMBRANE CARTRIDGES

Certified Pleated Polyethersulfone (PES) Membrane Cartridges

SWT's MPE Series filter cartridges are shipped with Quality Assurance Certificates with a formal efficiency claim of >99.9% at the rated pore size. They incorporate a modified asymmetric polyethersulfone membrane with polypropylene supports and hardware for enhanced service life and cleanliness in UPDI water and other microelectronics applications. Made in USA.



PART NUMBER MATRIX

SO-MPE-PES (MR) (A1) (A2) (NL) (SM)

(MR) Micron Rating

00 0.03 micron
01 0.1 micron
02 0.2 micron

(A1) End Adapter #1

A Flat end gasket
B 120 internal o-ring
C 213 internal o-ring
E 222 o-ring
F 226 o-ring
J 020 internal o-ring
Q 222 o-ring SS insert
Z 226 o-ring SS insert

(A2) End Adapter #2

A Flat end gasket
B 120 internal o-ring
C 213 internal o-ring
G Closed end cap
H Fin adapter

(NL) Nominal Length

10 10 inch (25.4 cm)
20 20 inch (50.8 cm)
30 30 inch (76.2 cm)
40 40 inch (101.6 cm)

(SM) Seal Material

B Buna-N
E EPDM
S Silicone
T Teflon Encapsulated
(only 222 & 226)
V Viton


Example: SO-MPE-PES02AA30S is a 0.2 micron absolute rated filter cartridge, 30 inch nominal length, double open end (DOE) configuration with silicone seals.

ABSOLUTE CARTRIDGES



MPE SERIES PES MEMBRANE CARTRIDGES

End Adapter Equivalent Codes



Without adapters




AA – Standard DOE
Code 1




JG – 020 int. o-ring / Closed end
Code 2 (M2)




EG – 222 o-ring / Closed end
Code 3 (M3)



FG – 226 o-ring / Closed end
Code 6 (M6)



FH – 226 o-ring / Fin adapter
Code 7 (M7)



EH – 222 o-ring / Fin adapter
Code 8 (M8)

Shipping Information

NOMINAL LENGTH		QUANTITY PER CARTON	APPROX. SHIP. WT.	
INCH	CM		LB	KG
10	25	18	15	6.8
20	51	16	24	10.9
30	76	6	13	5.9
40	102	6	17	7.7